SAT20 HA

HAND-HELD DISPENSER FOR HIGH BOND TAPE



Features	Benefits	Customer value
Cutting system with guillotine shear and automatic tape arrangement for the next use	The blade easily cuts any single-sided tape, double-sided tape or acrylic foam tape up to 20mm wide and 1.5mm thick. After each cut the tape is accurately positioned for the next use.	Single-sided, double-sided and acrylic foam tapes can be easily applied and cut with a single tool, removing the need for separate cutter, scissors and special rollers. There is no requirement to touch the tape during operations and the entire process becomes extremely quick, flawless and tidy.
Long structure in thin drawn metal	The dispenser can host up to 300m of tape without compromising its light weight and ensuring rapid operations.	Long and thick tapes are not a problem. The dispenser remains light despite its remarkable robustness. You will be able to work for longer without having to replace the tape and you will not experience the fatigue of using heavier dispensers.
Ergonomic handle with trigger recess	The carefully shaped handle allows you to hold the dispenser firmly and efficiently. The special protection avoids unpleasant fingerpinching accidents while working.	Using the dispenser is made easier and more comfortable by the ergonomic design. Working will be safer and fatigue-free.

SAT20 HA

Side handle and adjustable guide	The dispenser can be held very firmly and safely. The tape can be applied along a straight line with extreme precision.	Excellent precision even when applying the tape on challenging supports, like thin profiles or frames. You can apply pressure with both hands and always be sure of achieving high accuracy.
Rubber roller	The ideal roller for any tape, whether singlesided or double sided. The rubber roller ensures a flawless application, without unwanted bubbles and without any damage to the application zone.	You will be able, when required, to apply high pressure to any tape without damaging or scratching even the most delicate of base materials.
Adjustable brake	Enables precise setting of the tape tension.	Not all tapes require the same tension. By always selecting the optimal setting you will be able to obtain easier application without air bubbles and without creases.

Specifications

Code	Description	Max tape width (mm)	Max tape Ø (mm)	Roller Ø (mm)	Net weight (Kg)	Items per box
1 390 025	SAT 20 HA	20	320	3	0,905	2
1 391 025	SAT 20 LA	25	320	3	0,905	2