

R E G G E T T A L U C I D A E Z I N C A T A



Dimensioni		Resistenza	Carico di rottura		All	Peso rotolo	Avvolgimento	Finitura	Rotoli per pallet kg 580	Diametro Int / Est	Resa
mm	pollici	N/mm ²	N	Kg	%	Kg				mm	mt/kg
13 x 0.40	1/2 x 0.015	640	3328	339	2	16	monospira	lucida	36	300 / 540	24,50
13 x 0.45	1/2 x 0.018	640	3744	382	2	16	monospira	lucida	36	300 / 540	21,78
13 x 0.50	1/2 x 0.020	640	4160	424	2	16	monospira	lucida	36	300 / 540	19,60
13 x 0.60	1/2 x 0.024	640	4992	509	2	16	monospira	lucida / zincata	36	300 / 540	16,33
16 x 0.40	5/8 x 0.015	640	4096	417	2	19	monospira	lucida	30	300 / 540	19,90
16 x 0.45	5/8 x 0.018	640	4608	470	2	19	monospira	lucida	30	300 / 540	17,69
16 x 0.50	5/8 x 0.020	640	5120	522	2	19	monospira	lucida	30	300 / 540	15,92
16 x 0.60	5/8 x 0.024	640	6144	626	2	19	monospira	lucida / zincata	30	300 / 540	13,27
19 x 0.45	3/4 x 0.018	640	5472	558	2	19	monospira	lucida	30	300 / 540	14,90
19 x 0.50	3/4 x 0.020	640	6080	620	2	23	monospira	lucida	25	300 / 540	13,41
19 x 0.60	3/4 x 0.024	640	7296	744	2	23	monospira	lucida / zincata	25	300 / 540	11,17
19 x 0.70	3/4 x 0.027	640	8512	868	2	23	monospira	lucida	25	300 / 540	9,58
19 x 0.80	3/4 x 0.031	640	9728	992	2	23	monospira	lucida / zincata	25	300 / 540	8,38
25 x 0.80	1 x 0.031	640	12800	1305	2	30	monospira	lucida / zincata	18	300 / 540	6,37
25 x 0.90	1 x 0.035	640	14400	1468	2	30	monospira	lucida	18	300 / 540	5,66
25 x 1.00	1 x 0.039	640	16000	1631	2	30	monospira	lucida	18	300 / 540	5,10
32 x 0.50	1 1/4 x 0.020	640	10240	1044	2	38	monospira	lucida	15	300 / 540	7,96
32 x 0.60	1 1/4 x 0.024	640	12288	1253	2	38	monospira	lucida	15	300 / 540	6,63
32 x 0.80	1 1/4 x 0.031	640	16384	1670	2	38	monospira	lucida / zincata	15	300 / 540	4,98
32 x 0.90	1 1/4 x 0.035	640	18432	1879	2	38	monospira	lucida	15	300 / 540	4,92
32 x 1.00	1 1/4 x 0.039	640	20480	2088	2	38	monospira	lucida	15	300 / 540	3,98

Elettrozincatura: 2,5/2,5 my